

Abrasive mop disc
SMT 627
Advantages

Good stock removal rate on unalloyed steels ■ High edge stability ■ Also suitable for non-ferrous metals


Applications:

- Wood
- NF metals
- Steel

Design

Convex 12°

Quality class


Supra

Grain

Aluminium oxide

Backing plate

Glass fibre


Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	
			■	■		■	■		■																

Diameter x Bore in mm	Grit	Max. operating speed	Max. RPM	Packing unit/pcs.	Cat. number		
115 x 22,23	36	80 m/s	13,300 rpm	10	116329		
115 x 22,23	40	80 m/s	13,300 rpm	10	116330		
115 x 22,23	60	80 m/s	13,300 rpm	10	116332		
115 x 22,23	80	80 m/s	13,300 rpm	10	116333		
115 x 22,23	120	80 m/s	13,300 rpm	10	116334		
125 x 22,23	40	80 m/s	12,200 rpm	10	116337		
125 x 22,23	60	80 m/s	12,200 rpm	10	116339		
125 x 22,23	80	80 m/s	12,200 rpm	10	116340		
125 x 22,23	120	80 m/s	12,200 rpm	10	116341		
180 x 22,23	36	80 m/s	8,500 rpm	10	116342		
180 x 22,23	40	80 m/s	8,500 rpm	10	116343		
180 x 22,23	60	80 m/s	8,500 rpm	10	116345		
180 x 22,23	80	80 m/s	8,500 rpm	10	116346		