

Abrasive mop disc SMT 628

Advantages

High removal rate, also under low grinding pressure ■ Very good cutting performance especially for surface work on stainless steel ■ No clogging or glazing



Applications:

- Stainless steel
- Steel

Design

Flat

Quality class

Supra

Grain

Zirconia alumina

Backing plate

Glass fibre



Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	
			■	■	■	■	■		■																

Diameter x Bore in mm	Grit	Max. operating speed	Max. RPM	Packing unit/pcs.	Cat. number		
115 x 22,23	36	80 m/s	13,300 rpm	10	134434		
115 x 22,23	40	80 m/s	13,300 rpm	10	133923		
115 x 22,23	50	80 m/s	13,300 rpm	10	134435		
115 x 22,23	60	80 m/s	13,300 rpm	10	134436		
115 x 22,23	80	80 m/s	13,300 rpm	10	134437		
115 x 22,23	120	80 m/s	13,300 rpm	10	134438		
125 x 22,23	36	80 m/s	12,200 rpm	10	173804		
125 x 22,23	40	80 m/s	12,200 rpm	10	173805		
125 x 22,23	60	80 m/s	12,200 rpm	10	173807		
125 x 22,23	80	80 m/s	12,200 rpm	10	173808		
125 x 22,23	120	80 m/s	12,200 rpm	10	173809		
180 x 22,23	36	80 m/s	8,500 rpm	10	139844		
180 x 22,23	40	80 m/s	8,500 rpm	10	139719		
180 x 22,23	60	80 m/s	8,500 rpm	10	139847		
180 x 22,23	80	80 m/s	8,500 rpm	10	139846		
180 x 22,23	120	80 m/s	8,500 rpm	10	139845		

Abrasive mop disc

Abrasive mop disc
SMT 625

Advantages

Significantly higher abrasive performance and longer service life due to large number of flaps ■ Especially good cutting performance when used for surface work on stainless steel ■ No glazing

Applications:

- Stainless steel
- Steel

Design

Flat

Quality class


Special

Grain

Zirconia alumina

Backing plate

Plastic, glass-fibre reinforced


Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	
	■		■	■	■	■	■		■																

Diameter x Bore in mm	Grit	Max. operating speed	Max. RPM	Packing unit/pcs.	Cat. number		
115 x 22,23	24	80 m/s	13,300 rpm	10	2756		
115 x 22,23	36	80 m/s	13,300 rpm	10	2757		
115 x 22,23	40	80 m/s	13,300 rpm	10	2758		
115 x 22,23	50	80 m/s	13,300 rpm	10	2759		
115 x 22,23	60	80 m/s	13,300 rpm	10	2760		
115 x 22,23	80	80 m/s	13,300 rpm	10	2761		
115 x 22,23	120	80 m/s	13,300 rpm	10	3311		
125 x 22,23	40	80 m/s	12,200 rpm	10	254055		
125 x 22,23	60	80 m/s	12,200 rpm	10	254056		
125 x 22,23	80	80 m/s	12,200 rpm	10	254057		
180 x 22,23	24	80 m/s	8,500 rpm	5	2762		
180 x 22,23	36	80 m/s	8,500 rpm	5	2763		
180 x 22,23	40	80 m/s	8,500 rpm	5	2764		
180 x 22,23	60	80 m/s	8,500 rpm	5	2766		
180 x 22,23	80	80 m/s	8,500 rpm	5	2767		

Abrasive mop disc
SMT 645

Advantages

High edge stability ■ Very good removal rate also on low-power angle grinders ■ Long service life due to double grinding flaps



Applications:

- Stainless steel
- Steel

Design

Flat

Quality class


Supra

Grain

Zirconia alumina

Backing plate

Plastic



Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	
				■		■	■																		

Diameter x Bore in mm	Grit	Max. operating speed	Max. RPM	Packing unit/pcs.	Cat. number		
115 x 22,23	40	80 m/s	13,300 rpm	10	278590		
115 x 22,23	60	80 m/s	13,300 rpm	10	278591		
115 x 22,23	80	80 m/s	13,300 rpm	10	278592		