

**Backing pad
ST 358**

Advantages

Medium-hard backing pad allows good adaptation to the workpiece ■ For universal use, especially for surface and finish grinding (grit 50 and finer) ■ High temperature resistance

Suitable for disc diameter	Thread/ Shaft	Max. operating speed	Max. RPM	Packing unit/pcs.	Cat. number		
100 x 16	M 10	80 m/s	15,000 rpm	1	305190		
100 x 22	M 14	80 m/s	15,000 rpm	1	2774		
115 x 22	M 10	80 m/s	13,300 rpm	1	14859		
115 x 22	M 14	80 m/s	13,300 rpm	1	14838		
125 x 22	M 14	80 m/s	12,200 rpm	1	14835		
150 x 22	M 14	80 m/s	10,200 rpm	1	14836		
180 x 22	M 14	80 m/s	8,500 rpm	1	14840		
235 x 22	M 14	80 m/s	6,600 rpm	1	14841		

**Backing pad
ST 358 A**

Advantages

For rough grinding ■ Cool grinding ■ Increased aggressiveness due to hard, ribbed abrasive surface ■ High temperature resistance and stability

Suitable for disc diameter	Thread/ Shaft	Max. operating speed	Max. RPM	Packing unit/pcs.	Cat. number		
115	M 14	80 m/s	13,300 rpm	1	126346		
125	M 14	80 m/s	12,200 rpm	1	126347		
178	M 14	80 m/s	8,500 rpm	1	126348		