



Long shafted nylon plug for through fixing a wide range of products with a specially matched zinc & yellow screw.

Suitable for concrete, full brick and perforated bricks.

Pozi Drive
M8 = No3
M10 = No4

NYLON FRAME FIXINGS

Code	Size	Anchor Hole Size	Anchor Plug Length	Fastens Up To	Min Hole Depth	Rec Tensile kN	Rec Shear kN	Qty Per Box	Qty Per Outer	Weight Kg Per 100	Price £ Per 100
0835M540060	8 x 60	8	60	20	70	0.5	0.5	50	1200	1.29	18.92
0835M540080	8 x 80	8	80	40	90	0.5	0.5	50	1200	1.61	23.96
0835M540100	8 x 100	8	100	50	110	0.5	0.5	50	1100	1.96	25.96
0835M540120	8 x 120	8	120	70	130	0.5	0.5	25	600	2.36	36.25
0835M540135	8 x 140	8	140	90	150	0.5	0.5	25	600	2.70	39.35
0835M560080	10 x 80	10	80	30	90	0.6	0.6	25	600	2.40	34.68
0835M560100	10 x 100	10	100	50	110	0.6	0.6	25	600	3.02	39.35
0835M560115	10 x 120	10	120	70	130	0.6	0.6	20	480	3.88	47.28
0835M560135	10 x 135	10	140	90	150	0.6	0.6	20	480	4.98	55.36
0835M560160	10 x 160	10	160	110	170	0.6	0.6	20	480	5.38	72.11



Recommended where a rapid fix and a large number of fixings are required.

This plug can be used for quick installation in internal and external construction work.

Suitable for concrete natural stone and solid brick masonry.

Zinc or stainless steel screws available.

HAMMER FIXINGS

Code	Size	Anchor Hole Size	Anchor Plug Length	Fastens Up To	Min Hole Depth	Rec Tensile kN	Rec Shear kN	Qty Per Box	Qty Per Outer	Weight Kg Per 100	Price £ Per 100
0837M470030	5 x 30	5	30	5	40	0.16	0.18	100	3500	0.25	7.16
0837M470045	5 x 40	5	40	15	55	0.18	0.20	100	3500	0.40	7.48
0837M490040	6 x 40	6	40	10	50	0.20	0.20	100	3500	0.38	7.25
0837M490055	6 x 60	6	60	25	65	0.22	0.22	100	2400	0.54	8.75
0837M490070	6 x 70	6	70	40	80	0.22	0.22	100	2400	0.70	11.17
0837M540060	8 x 60	8	60	12	67	0.32	0.30	50	1750	0.94	13.95
0837M540075	8 x 80	8	80	30	85	0.32	0.30	50	1750	1.26	15.23
0837M540100	8 x 100	8	100	60	110	0.32	0.30	50	1200	1.60	23.26
0837M540120	8 x 120	8	120	80	130	0.32	0.30	50	1200	1.92	25.12
0837M540135	8 x 135	8	135	95	145	0.32	0.30	50	1200	2.16	27.64




Ideal for quick installation and with stainless steel screws for added corrosion resistance.


HAMMER FIXINGS - Stainless Steel Screw A2-304

Code	Size	Anchor Hole Size	Anchor Plug Length	Fastens Up To	Min Hole Depth	Rec Tensile kN	Rec Shear kN	Qty Per Box	Weight Kg Per 100	Price £ Per 100
0837M490040SS	6 x 40	6	40	10	50	1.00	1.00	100	0.47	25.93
0837M540100SS	8 x 100	8	100	60	110	1.10	1.50	100	1.56	66.55


Loads are for 25 N/mm² CONCRETE.




Drill your hole to the correct diameter...



...clear any debris...



...insert fixing into hole...



...tighten to complete fixing process.



PLASTIC WALL PLUGS

Code	Colour	Hole Size	Plug Length	Woodscrew Gauge	Woodscrew Size	Min Hole Depth	Qty Per Box	Qty Per Outer	Weight Kg Per 100	Price £ per 1000
0948TBROWN	Brown	7	37	No. 10-14	5.0-6.0	46	100	1000	1.08	17.62
0948TRED	Red	6	30	No. 6-10	3.5-5.0	37	100	1000	0.70	13.89
0948TYELLOW	Yellow	5	25	No. 4-6	3.0-3.5	30	100	1000	0.37	13.19
0948TBLUE	Blue	10	50	No. 14-18	6.0-8.0	55	100	1000	1.30	52.09

All purpose cost effective fixings for light to medium applications.

Manufactured to British standard lengths for the professional tradesman. Soft and pliable for cold site use (made with premium HDPE).



NYLON WALL PLUGS - Suitable for solid base

Code	Size	Anchor Hole Size	Plug Length	Screw Gauge	Screw Size	Min Hole Depth	Rec Tensile Load kN	Qty Per Box	Weight Kg Per 100	Price £ per 100
0947E525	5 x 25	5	25	4-6G	2.5-3.5	35	0.20	200	0.04	1.47
0947E630	6 x 30	6	30	6-10G	3.5-5.0	40	0.30	100	0.08	1.88
0947E730	7 x 30	7	30	8-12G	4.5-5.0	40	0.35	100	0.12	2.74
0947E840	8 x 40	8	40	10-14G	5.0-6.0	55	0.45	100	0.15	2.77
0947E1050	10 x 50	10	50	14-18G	6.0-8.0	65	0.90	50	0.29	7.08
0947E1260	12 x 60	12	60	18-24G	8.0-10.0	75	1.10	25	0.52	8.21
0947E1475	14 x 75	14	75	24-32G	10.0-12.0	90	1.90	20	0.74	15.01

Rimless plugs, ideal for fixing wall lights, shelving and cupboards. Often used with coach screws as satellite fixings.



UNIVERSAL NYLON WALL PLUGS - Suitable for hollow or solid base

Code	Size	Anchor hole size	Plug length	Screw Gauge	Screw Size	Min Hole Depth	Rec Tensile Load kN	Qty Per Box	Weight Kg Per 100	Price £ per 100
0947TPF637	6 x 37	6	37	6-8G	3.5-4.0	50	0.14	100	0.04	4.00
0947TPF850	8 x 50	8	50	10-12G	4.5-5.5	60	0.20	50	0.12	6.04
0947TPF1060	10 x 60	10	60	12-14G	6.0-8.0	70	0.30	25	0.15	8.10

Universal plugs used in lightweight, aerated and hollow blockwork giving quicker and greater expansion than standard wall plugs.



NAIL IN ANCHORS - Zinc Alloy

Code	Size	Anchor Hole Size	Anchor Length	Fastens Up To	Head Diameter	Rec Tensile Load kN	Rec Shear Load kN	Qty Per Box	Weight Kg Per 100	Price £ per 100
0842T490030	6 x 30	6	30	10	13	1.1	1.40	100	1.05	14.06
0842T490040	6 x 40	6	40	20	13	1.1	1.40	100	1.18	16.56
0842T490050	6 x 50	6	50	30	13	1.1	1.40	100	1.50	18.86


Pre-assembled for quick and repetitive hammer action installation offering simple through fixing.

CONCRETE SCREWS - T30 drive bit and cover cap in every box


Code	Size	Drill Size	Screw Length	Fastens Up To	Min Hole Depth	Rec Tensile Load Kn	Rec Shear Load Kn	Qty Per Box	Weight Kg Per 100	Price £ Per 100
0869T7560	7.5 x 60	6	60	20	45	2.0	2.5	100	1.45	16.96
0869T7580	7.5 x 80	6	80	40	45	2.0	2.5	100	1.72	22.19
0869T75100	7.5 x 100	6	100	60	45	2.0	2.5	100	2.53	24.82
0869T75120	7.5 x 120	6	120	80	45	2.0	2.5	100	2.93	33.99
0869T75150	7.5 x 150	6	150	110	45	2.0	2.5	100	3.16	41.29

Countersunk self tapping screw, zinc & yellow plated for use in concrete block and masonry, ideal alternative in fixing frames.


- Neat Firm Fixing
 - Door and Window Frames
- uPVC and Aluminium
- Dense Concrete
- Solid Brick
- Perforated Bricks
- Aircrete
- Natural Stone




Drill the correct diameter.



Position the self tapping concrete screw.



Insert screw though and...



... fit cover cap if required.

NYLON WINDOW FRAME ANCHOR - with white cover caps

Code	Size	Anchor Hole Size	Anchor Plug Length	Fastens Up To	Min Hole Depth	Rec Tensile Load kN	Rec Shear Load Kn	Qty Per Box	Qty Per Outer	Weight Kg Per 100	Price £ Per 100
0836M540100	8 x 100	8	100	50	60	0.8	1.0	50	500	1.63	21.44
0836M540120	8 x 120	8	120	70	60	0.8	1.0	50	500	2.09	25.84
0836M540140	8 x 140	8	140	90	60	0.8	1.0	50	500	2.34	32.19
0836M560075	10 x 75	10	75	15	70	1.3	1.5	50	500	1.74	25.08
0836M560100	10 x 100	10	100	40	70	1.3	1.5	50	500	2.39	27.14
0836M560120	10 x 120	10	120	60	70	1.3	1.5	50	500	2.93	33.93

For mounting uPVC window frames to brickwork and masonry.



METAL WINDOW FRAME ANCHOR - with white cover caps

Code	Size	Anchor Hole Size	Anchor Plug Length	Fastens Up To	Min Hole Depth	Rec Tensile Load kN	Rec Shear Load Kn	Qty Per Box	Qty Per Outer	Weight Kg Per 100	Price £ Per 100
0838T560075	10 x 72	10	70	40	50	-	-	100	500	3.3	42.17
0838T560092	10 x 92	10	90	60	50	-	-	100	500	3.9	46.68
0838T560112	10 x 112	10	110	80	50	-	-	100	500	4.6	50.82
0838T560132	10 x 132	10	130	100	50	-	-	100	500	5.3	55.37
0838T560152	10 x 152	10	150	140	50	-	-	100	500	5.9	64.37

Fixes door and window frames to most building materials.

All steel for strength and durability.

