

# MITRE SAWS

## 01504 Sliding Compound Mitre Saw 12" / 305mm Double Bevel Action, Belt Drive

trade level ☆☆

A powerful saw with a 2000w belt driven motor for smoother, quieter operation and extended life. This 12" saw is ultra-versatile, with double bevel action 45° left and right. The 305mm blade allows a impressive straight-cut cutting capacity of 340mm width x 102mm depth. Laser guidance improves cutting accuracy.

- Adjustable depth stop for tenoning or trenching
- Sturdy rotating table with pre-set stops: 0°, 15°, 22.5°, 30° and 45°
- Dust extraction bag for cleaner, safer use

- Belt driven - for smoother quieter operation and extended motor life
- Automatic retracting lower guard for increased safety



Super smooth sliding action, with lock facility



Laser guidance for improved accuracy



Double bevel facility 45° left and right



Search YouTube for:  
SipTechZone

- 13AMP SUPPLY
- DOUBLE BEVEL ACTION
- BELT DRIVE
- LASER GUIDANCE

SLOW RUNNING

BELT DRIVE FOR SMOOTHER OPERATION



Don't Forget ACCESSORIES & CONSUMABLES Page 207



Don't Forget SAW STANDS & BENCHES Pages 195 - 197

ITEM NO.	01504
Motor	2kW (2.7hp)
Supply	230v (13amp)
Mitre Range	-45° / 0° / +45°
Cutting Capacities:	
Straight Cut @ 0° x 0°	340 x 102mm
Mitre Cut @ 45° x 0°	240 x 102mm
Left Bevel Cut @ 0° x 45°	340 x 55mm
Right Bevel Cut @ 0° x 45°	340 x 40mm
Left Compound Mitre Cut @ 45° x 45°	240 x 55mm
Right Compound Mitre Cut @ 45° x 45°	240 x 40mm
Blade Diameter	305mm
Blade Bore	30mm
Blade Teeth / Type	40 / TCT
Blade Speed	4500rpm
Gross Weight	21kg
Packaged Dimensions (HxWxD)	530 x 575 x 910mm
Barcode Number	5012713015047

## 01511 Sliding Compound Mitre Saw 10" / 254mm - with Laser

trade level ★★

The brand new SIP 10" Sliding Compound Mitre Saw presents fantastic versatility coupled with excellent value-for-money. With an integrated laser for added accuracy, the saw also boasts large cutting capacities cutting straight, mitre, left and right bevel and left and right compound mitre cuts.

- Powerful 2000w motor
- Integrated laser for added accuracy
- Automatically retracting lower blade guard for added safety
- Adjustable depth stop for tenoning and trenching
- Dust extraction bag for cleaner, safer use
- Sliding action for increased cutting capacity
- Pre-set stops at the common mitre angles (left & right)  
0°, 15°, 22.5°, 30° & 45°



**NEW**  
FROM SIP

13AMP SUPPLY

LASER GUIDANCE

ITEM NO.	01511
Motor	2KW (2.7hp)
Supply	230v (13amp)
Mitre Range	-45° / 00° / +45°
Cutting Capacities:	
Straight Cut @ 0° x 0°	340 x 80mm
Mitre Cut @ 45° x 0°	240 x 80mm
Bevel Cut @ 0° x 45°	340 x 50mm
Compound Mitre Cut @ 45° x 45°	240 x 50mm
Blade Diameter	254mm
Blade Bore	30mm
Blade Teeth / Type	40 / TCT
Blade Speed	5500rpm
Gross Weight	18kg
Packaged Dimensions (HxWxL)	390 x 550 x 810mm
Barcode Number	5012713015115

## 01928 Variable Speed Scroll Saw 16" / 406mm - with Laser

trade level ★★

The SIP Scroll Saw has a parallel arm design and is perfect for cutting intricate curves while keeping an accurate 90° edge. The robust, cast iron, rounded edge table can be tilted 45° to the left and right. To keep machine down time to a minimum, the machine has a quick-change blade system. A useful feature of the saw is its variable speed allowing adjustment to suit the task and material in hand. Slower speeds can be used for the cutting of plastic and non-ferrous metals, while faster speeds can be used for cutting wood up to 50mm thick.

- Cast iron round ended table can be tilted 45° left and right
- Flexible dust blower for fast and easy clearing of saw dust
- Integrated fully adjustable LED light
- Laser guidance ensures accuracy
- Adjustable safety guards - safe and unhindered cutting



Cast iron table, tilts 0° to 45° left and right

13 AMP SUPPLY

NVR SWITCH

LASER GUIDANCE

Don't Forget ACCESSORIES & CONSUMABLES Page 209

ITEM NO.	01928
Motor	120w
Supply	230v (13amp)
Max. Depth of Cut	50mm
Cutting Stroke	15mm
Speeds	400 - 1600 stroke/min
Table Size	420 x 270mm
Table Tilt	0° - 45° (left & right)
Throat Size	406mm
Net Weight	17kg
Packaged Dimensions (HxWxL)	670 x 280 x 420mm
Barcode Number	5012713019281