05290 Startmaster T200/30W

05294 Startmaster T400/75W 05296 Startmaster T600/90W

Our excellent range of Trade Starter / Chargers, wheel mounted for easy manoeuvrability.



MODEL	STARTMASTER T200/30W	STARTMASTER T400/75W	STARTMASTER T600/90W
ITEM NO.	05290	05294	05296
Supply	230v (13amp)	230v (40amp)	230v (40amp)
Charging Voltage/s	12v / 24v	12v / 24v	12v / 24v
Charge Rate Settings	4	4	4
Max. Charging Current Output	30amp	75amp	90amp
Max. Start Current	180amp	400amp	570amp
Min. Battery Capacity	20Ah	20Ah	20Ah
Degree of Protection	IP20	IP20	IP20
Cable Length	2 metres	2 metres	2 metres
Net Weight	15kg	23kg	28kg
Gross Weight	17kg	25kg	30kg
Packaged Dimensions (HxWxL)	345 x 300 x 505mm	340 x 300 x 510mm	330 x 425 x 630mm
Barcode Number	5012713052905	5012713052943	5012713052967

trade level ★★

PROFESSIONAL Starter / Chargers

Key features
Built with tough steel case, these units are ideal for use in busy workshops and

- Heavy duty charge leads and crocodile clips
- Reverse polarity protection



05532 Startmaster P300

A reliable, professional starter/charger - perfect for all garages and workshops.

• Ammeter clearly and accurately indicates charging levels

2 charge rate levels - for fast and slow charging

150 amp







professional level ***



13 AMP

ITEM NO.	05532
Supply	230v (13amp)
Charging Voltage/s	12v
Max. Rated Battery Capacity	160Ah
Rated Charge Output	14amps
Max. Rated Charge Output	20amps
Boost @ 1V/c	85amps
Max. Boost	150amps
Charge Rate Settings	2
Degree of Protection	IP20
Insulation Class	Class F
Weight	6.58kg
Packaged Dimensions (HxWxL)	245 x 265 x 300mm
Barcode Number	5012713055326

professional level ★★★



05533 Startmaster P440

A reliable, professional starter/charger - perfect for all garages and workshops.

- Ammeter clearly and accurately indicates charging levels
- 2 charge rate levels for fast and slow charging



STARTMASTER P300

13 AMP SUPPLY

05533 230v (13amp) Supply 12v / 24v 180Ah Charging Voltage/s Max. Rated Battery Capacity Rated Charge Output 22amps Max. Rated Charge Output Boost @ 1V/c 33amps 135amps Max. Boost 220amps Charge Rate Settings IP20 Degree of Protection Class F 12.7kg Insulation Class Weight Packaged Dimensions (HxWxL) 410 x 295 x 315mm Barcode Number 5012713055333









05534 Startmaster PW520

A reliable, professional starter/charger - perfect for all garages and workshops.

- Ammeter clearly and accurately indicates charging levels
- 3 charge rate levels for fast and slow charging





ITEM NO.	05534
Supply	230v (13amp)
Charging Voltage/s	12v / 24v
Max. Rated Battery Capacity	200Ah
Rated Charge Output	25amps
Max. Rated Charge Output	42amps
Boost @ 1V/c	145amps
Max. Boost	260amps
Charge Rate Settings	3
Degree of Protection	IP20
Insulation Class	Class F
Weight	21kg
Packaged Dimensions (HxWxL)	360 x 400 x 700mm
Barcode Number	5012713055340





Made in Italy

PROFESSIONAL Starter / Chargers

05535 Startmaster P560

A reliable, professional starter/charger - perfect for all garages and workshops.

- Ammeter clearly and accurately indicates charging levels
- 2 charge rate levels for fast and slow charging













05536 Startmaster PW600

A reliable, professional starter/charger - perfect for all garages and workshops.

- Ammeter clearly and accurately indicates charging levels
- 3 charge rate levels for fast and slow charging



ITEM NO.	05536
Supply	230v (16amp)
Charging Voltage/s	12v / 24v
Max. Rated Battery Capacity	280Ah
Rated Charge Output	30amps
Max. Rated Charge Output	45amps
Boost @ 1V/c	200amps
Max. Boost	300amps
Charge Rate Settings	3
Degree of Protection	IP20
Insulation Class	Class F
Weight	21kg
Packaged Dimensions (HxWxL)	360 x 400 x 700mm
Barcode Number	5012713055364

professional level ★★★

professional level ★★★

professional level ★★★

13 AMP









05537 Startmaster PW760

A reliable, professional starter/charger - perfect for all garages and workshops.

- Ammeter clearly and accurately indicates charging levels
- 3 charge rate levels for fast and slow charging



ITEM NO.	05537
Supply	230v (20amp)
Charging Voltage/s	12v / 24v
Max. Rated Battery Capacity	340Ah
Rated Charge Output	38amps
Max. Rated Charge Output	57amps
Boost @ 1V/c	260amps
Max. Boost	380amps
Charge Rate Settings	3
Degree of Protection	IP20
Insulation Class	Class F
Weight	25kg
Packaged Dimensions (HxWxL)	360 x 400 x 700mm
Barcode Number	5012713055371







PROFESSIONAL Starter / Chargers

05538 Startmaster PW1000

A reliable, professional starter/charger - perfect for all garages and workshops.

- Ammeter clearly and accurately indicates charging levels
- 6 charge rate levels for fast and slow charging
- 120 minute variable charge timer facility for added convenience



professional level ***

05538 Supply 230v (25amp) Charging Voltage/s Max. Rated Battery Capacity 370Ah Rated Charge Output Max. Rated Charge Output 45amps Boost @ 1V/c 330amps 500amps Max. Boost Timer 120min Charge Rate Settings Degree of Protection IP20 Class F

Insulation Class Weight

Barcode Numbe

Packaged Dimensions (HxWxL)

Max. Rated Charge Output

Boost @ 1V/c Max. Boost

Remote Start

Charge Rate Settings
Degree of Protection

Packaged Dimensions (HxWxL)

Insulation Class

Barcode Number

Weight

professional level **



05539 230v (40amp) 12v / 24v

400Ah 60amps

90amps 400amps

700amps

120min

IP20

32kg

Class F

370 x 390 x 745mn

5012713055395

29kg 370 x 390 x 745mm

5012713055388

500 amp







05539 Startmaster PW1400

A reliable, professional starter/charger - perfect for all garages and workshops.

- Ammeter clearly and accurately indicates charging levels
- 6 charge rate levels for fast and slow charging
- 120 minute variable charge timer facility for added convenience
- Remote lead for one man operation













· Easy-to-read digital display showing battery voltage, battery charge percentage charge time remaining and current

· Suitable for Lead Acid, AGM, Calcium or Gel batteries

- Variable timer for up to 10 hour charging
- · Infinitely variable charge current



05541 **Trolley for** Digital P900

professional level ★★★

Wheeled trolley

Storage shelves Barcode Number: 5012713055418

ITEM NO. Supply 230v (16amp) Charging Voltage/s Max. Rated Battery Capacity 375Ah Rated Charge Output Boost @ 1V/c 1 to 30amps 300amps Max. Boost 450amps Timer 10hrs Charge Rate Settings Degree of Protection IP20 Insulation Class Weight 20.1kg Packaged Dimensions (HxWxL) 260 x 380 x 440mm 5012713055401





Made in Italy